

FL-150

Nr. O-115

A water-dilutable non-sticking preparation removing grease, tar and bituminous mass

Packaging:

- 25 L barrel
- 200 L barrel
- Another packaging on customer's request

Application:

All industry sectors, particularly well-suited for contamination in the metal and road industry when cleaning machinery and equipment. It removes the bituminous mass, tar, lubricants, oils, fuels and softens very difficult, baked and persistent dirt so that it is easy to remove.

Properties:

- a pleasant orange smell,
- very high cleaning efficiency,
- removes the bituminous mass,
- it does not drip from vertical surfaces up to 8 hours (!),
- water-dilutable in the proportion of 1: 4 (the most effective action),
- chemically stable.

How to use:

- use the product in a sprayer with a capacity larger than 8L;
- spray the emulsion formed after dilution on the cleaned surface;
- leave for 15-30 minutes;
- rinse thoroughly with water under pressure;
- to obtain the best consistency, always add water to the concentrate, not the other way round.

Technical data:

Colour	colourless
Odour	orange, citrus
pH	non-applicable
Freezing temperature	< -10°C
Flash point (concentrate)	> 68°C
Boiling point	ok. 200°C
Explosive properties	non-explosive
Auto-ignition temperature	not available
Vapour pressure	> 0.01 kpa